DXA/DXB-1V(W)1A1J/1V(W)1A1J-X

PINOUT DIAGRAM

STATUS INDICATORS
1. POWER (GREEN)
2. NA

STATUS INDICATORS
1. TX CARRIER (GREEN)/ERROR (RED)

VIDEO INPUT (CH.1)
STATUS INDICATORS
1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

AUDIO INPUT/OUTPUT (PORT 3)
(DB-9 FEMALE)
1. (CH.1) OUTPUT-
2. (CH.1) OUTPUT+
3. NA
4. NA
5. GND
6. (CH.1) INPUT-
7. (CH.1) INPUT+
8. NA
9. NA

DATA RS485 IN/OUT (PORT 4)
(DB-9 FEMALE)
1. (CH.1) INPUT/OUTPUT +
2. (CH.1) INPUT/OUTPUT-
3. NA
4. NA
5. GND
6. NA
7. NA
8. NA
9. NA



OPTICAL PORT
STATUS INDICATORS
1. NA
2. RX OPTICAL SIGNAL (GREEN)/ABSENT (RED)
3. RX CARRIER (GREEN)/ERROR (RED)

VIDEO OUTPUT (CH.2)
STATUS INDICATORS
1. SYNC PRESENT (GREEN)
2. VIDEO PRESENT (GREEN)/OVERLOAD (RED)

STATUS INDICATORS (PORT 3)
1. (CH.1) AUDIO INPUT PRESENT
2. (CH.1) AUDIO INPUT OVERLOAD
3. NA
4. NA
5. (CH.1) AUDIO OUTPUT PRESENT
6. (CH.1) AUDIO OUTPUT OVERLOAD
7. NA
8. NA

STATUS INDICATORS (PORT 4)
1. (CH.1) DATA INPUT
2. (CH.1) DATA OUTPUT
3. NA
4. NA
5. NA
6. NA
7. NA
8. NA

MERIDIAN TECHNOLOGIES INC.
FILE NAME: 1V1A1J-1V1A1J.DWG
09/07/2005 V.1