


Digital Two Channel 10-Bit Video Multiplexer
 with Two Full Duplex RS-485 (4-wire) Data
 and Two Bi-Directional Contact Closure



FEATURES:

- 10 Bit Video Digital Encoding
- Real Time Video & Data Transmission
- 2 Bi-Directional Contact Closure Channels
- User-selectable, Contact Mapping (N.O, N.C)
- 7 MHz Video Bandwidth
- Meets RS-250C Short Haul Transmission Specifications
- NTSC, PAL, SECAM Compatible
- Two Bi-directional RS-485 (4-wire) Data Channels
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for Multimode and Singlemode
- Surface Mount Technology (SMT) for High Reliability and Repeatability
- *SpectraSmart™* Network Management Compatible
- Local LED Status Indicators to Monitor Critical System Diagnostics for Performance Parameters
- ST, FC Optical Connectors
- Hot Swappable Cards
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range
- 75 Ohm BNC Video Connector (Gold Center Pin)
- Meets EIA RS-170, RS-343A Formats
- DB 9 Type Connectors for Data
- DB15 Type Connectors for Contact Closure



DESCRIPTION:

The DT/DR-2W2C2K/2C2K-x product incorporate digital encoding technology. This fiber optic module transmits two real-time, simplex 10-bit Video & two full-duplex RS-485 (4-wire) Data and 2 Bi-Directional Contact Closure channels over one optical fiber.

Both Multimode and Singlemode fiber versions are available. The Contact Closure channels can be configured as either Normally Open (N.O.) or Normally Closed (N.C.).

Meridian's digital product line incorporates plug-in personality signal cards to easily configure a wide variety of module types.

The functionality of the DT/DR-2W2C2K/2C2K-x series products is enhanced by their compatibility with Meridian's PC based SpectraSmart™ Network Management & Diagnostic Software system. SpectraSmart supervises the operating parameters of the transmission system such as the status on video levels, sync, digital carrier detect, voltages, temperatures, optical levels etc. See SpectraSmart brochure for further details.

CONFIGURATIONS:

The DigiFlex™ product family is available as rack mounted cards that can be installed in either Meridian's desk chassis or in 19" racking frames. This system can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be made a standalone system by using the SR-1000/s, 2 slot desk / wall mount chassis (87 VAC- 264VAC)

MARKETS:

- ✓ Intelligent Transportation Systems (ITS)
- ✓ Security and Surveillance
- ✓ Access Control

SPECIFICATIONS:

Video

Format	NTSC, PAL, SECAM
Voltage/Impedance	1 Vp-p, 75 Ohm, 1.5 Vp-p max.
Bandwidth	5 Hz to 6.8 MHz @ -3 dB
Differential Gain	<0.6%
Differential Phase	<0.3°
SNR	>67 dB (weighted)*
Return Loss	>30 dB
Field Tilt	< 0.5%

Data

Formats	RS-485 (4-wire)
Data Rate	DC to 250 Kb/s
Bit Error Rate	10 ⁻⁹ *

Contact Closure

Format	Normally Open (N.O.) or Normally Closed (N.C.) - jumper selectable
Rate	10 Hz.(Per Channel)
Contact Rating	0.3A, 30V AC / DC
Contact Bounce Time	5 ms

Connectors

Video	75 Ohm BNC (Gold Center Pin)
Optical	ST, FC
Power (module)	See SR-1000 Brochure for details
Data	DB9 Female
Contacts	DB9 (HD) Female

Optical

Fiber Data Rate	500 Mb/s
-----------------	----------

Power **

Card	9 Watts
------	---------

Indicators (LEDs)

1 - Green	Power On
1 - Bi-color	TX Carrier/ Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
1 - Green	RX Optical Signal -Present/Absent
2 - Bi-color	Video Present / Overload
2 - Green	Video Sync. Present
4 - Green	Data Present
2 - Green	Transmit Contact Closure
2 - Green	Recieve Contact Closure

Physical

Dimensions (Card)	160 mm (6.3") L, 127 mm (5") H
	44mm (0.80")W
Weight (Card)	450 gms (16 Oz)
No. of Slots	2


Enviromental

Operating Temperature	-40°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing

Quality


MTBF	>170,000 hours @ Ground Fix 35°C per MIL217F
------	---

Part Numbers:



* measured @ max. optical budget

** Due to variations of drivers and diagnostic options, power shown @ max. value



OPTICAL:

Meridian Optical Code	Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)	Max Distance (Km)
2	Multimode (Laser) 62.5 / 125	-3	-23	20	1300 / 850	ST	23	2
5	Single-mode (FP Laser) 9 / 125	-3	-23	20	1310 / 1550	ST, FC	23	55

Meridian Technologies Inc.

700 Elmont Road. • Elmont, NY 11003 • 516. 285. 1000 • FAX 516. 285. 6300 • E-mail sales@meridian-tech.com
www.meridian-tech.com

ver. 05/2016 A