


## Digital 4 Channel Video Multiplexer with Return Manchester, RS-422 or Bi-Phase



### FEATURES:

- Standard 8 Bit Video Digital Encoding
- 4 Real-Time Video Signals w/ Return Data
- RS-422, Manchester or Bi-Phase
- 7 MHz Video Bandwidth
- Meets RS-250C Transmission Specifications
- NTSC, PAL, SECAM Compatible
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for Multimode and Single-mode
- Surface Mount Technology (SMT) for High Reliability and Repeatability
- SpectraSmart™ Network Management Compatible
- Local LED Status Indicators to Monitor Critical System Diagnostics for Performance Parameters
- ST, FC Optical Connector
- Hot Swappable Cards
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range
- Meets NEMA TS1 / TS2 & CALTRANS Specs.
- 75 Ohm BNC Video Connector (Gold Center Pin)
- Meets EIA RS-170, RS-343A Formats
- DB 9 Type Connector for Data
- DC to 1 Mb/s Data Rate

### DESCRIPTION:

The DT/DR-4V/1F series is a reliable, cost effective, state-of-the-art, one fiber, Bi-directional Digital Video and Data transmission system. This fiber optic system transmits four channels of real-time 8 bit video with a return channel of data over one Singlemode or Multimode fiber. The DT/DR-4V/1F accepts PAL, SECAM, or NTSC formats. The functionality of DT/DR-4V/1F series are further enhanced by their compatibility with Meridian's PC based SpectraSmart, Network Management and Remote Diagnostic Software System. SpectraSmart supervises the operating parameters of the transmission system such as status on video levels, sync, carrier detect, voltage, temperature, optical levels, data activity etc.. See the SpectraSmart brochure for more details.

Note: 10 bit version available. See DV-4W/1F series.

### CONFIGURATIONS:

The DT/DR-4V/1F product family is available as rack mount cards and modules that can be installed in all of Meridian's card chassis, desk chassis and 19" racking frames. This system can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be made a standalone system by using the SR-1000/s, 2 slot desk / wall mount chassis (87VAC-264VAC)

### MARKETS:

- ✓ Security and Surveillance
- ✓ Intelligent Transportation System (ITS)
- ✓ Access Control Systems
- ✓ Campus Lecture Networks
- ✓ Pro. Video / Audio

## SPECIFICATIONS:

### Video

Format	NTSC, PAL, SECAM
Voltage/Impedance	1 Vp-p, 75 Ohm, 1.5 Vp-p max.
Bandwidth	5 Hz to 6.8 MHz @ -3 dB
Differential Gain	<0.6%
Differential Phase	<0.3°
SNR	>60 dB (weighted)*
Return Loss	>30 dB
Field Tilt	< 0.5%

### Indicators (LEDs)

1 - Green	Power On
1 - Bi-color	TX Carrier/ Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
1 - Bi-color	RX optical signal - Present / Absent
4 - Bi-color	Video Present / Overload
4 - Green	Sync. Present
1 - Green	Data Present

### Data

Formats	RS-422, Manchester, Bi-Phase
Rate	DC to 1Mb/s
Bit Error Rate	10 <sup>-9</sup> *

### Physical

Dimensions:	
Card	160 mm (6.3") L, 100 mm (4") W 44 mm (1.7") H
Weight:	
Card	450 gms (16 Oz)
No. of Slots	2

### Optical

Fiber Data Rate	500 Mb/s
-----------------	----------

### Connectors

Video	75 Ohm BNC (Gold Center Pin)
Optical	ST, FC
Power	See SR-1000 Brochure for details
Data	DB9 Female

### Environmental

Operating Temperature	-34°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing

### Quality

MTBF	>240,000 hours @ Ground Fix 35°C per MIL217F
------	---

\* measured @ max. optical budget

\*\* Due to variations of drivers and diagnostic options, power shown @ max value

### Power \*\*

Card	9 Watts
------	---------

### Part Numbers:

DT-4V / 1F-2. . . . .	Transmitter, 850nm/ 1300nm, MM, Laser	DR-4V / 1F-2. . . . .	Receiver, 1300nm/ 850nm, MM, Laser
DT-4V / 1F-5. . . . .	Transmitter, 1310nm/1550nm, SM, Laser	DR-4V / 1F-5. . . . .	Receiver, 1550nm/1310nm, SM, Laser
DT-4V / 1F-8. . . . .	Transmitter, 1310nm/1550nm, SM, DFB Laser	DR-4V / 1F-8. . . . .	Receiver, 1550nm/1310nm, SM, DFB Laser



## OPTICAL:

Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)
Multimode (FP Laser) 62.5 / 125	-3	-23	20	1300 / 850	ST	23
Singlemode (FP Laser) 9 / 125	-3	-23	20	1310 / 1550	ST, FC	23
Singlemode (DFB Laser) 9 / 125	+3	-23	26	1310 / 1550	ST, FC	23

Meridian Technologies Inc.

700 Elmont Road. • Elmont, NY 11003 • 516. 285. 1000 • FAX 516. 285. 6300 • E-mail sales@meridian-tech.com  
Visit our web site: www.meridian-tech.com or www.meridian-tech.tv

ver 01/03