


**Digital 4 Channels 8-Bit Video
 Multiplexer with 4 Channels Return
 RS-422, Manchester or Bi-Phase**

FEATURES

- 8-Bit Video Digital Encoding
- 4 Real-Time Video Signals with 4 Channels of Return Data
- RS-422, Manchester or Bi-Phase
- 7 MHz Video Bandwidth
- Meets RS-250C Transmission Specifications
- NTSC, PAL, SECAM Compatible
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for Multimode and Single-mode
- Surface Mount Technology (SMT) for High Reliability and Repeatability
- SpectraSmart™ Network Management Compatible
- Local LED Status Indicators to Monitor Critical System Diagnostics for Performance Parameters
- ST, FC Optical Connector
- Hot Swappable Cards
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range
- Meets NEMA TS1 / TS2 & CALTRANS Specs.
- 75 Ohm BNC Video Connector (Gold Center Pin)
- Meets EIA RS-170, RS-343A Formats
- DB 9 Type Connector for Data
- DC to 1 Mb/s Data Rate

DESCRIPTION

The DT/DR-4V/4F-x product are reliable, cost effective, state-of-the-art, one fiber, Bi-directional Digital Video and Data transmission system.

This fiber optic system transmits four channels of real-time 8-bit or 10-bit Video with a return four channels of RS-422, Manchester or Bi-Phase data over one Singlemode or Multimode fiber.

The DT/DR-4V/4F-x accepts PAL, SECAM, or NTSC formats. The functionality of DT/DR-4V/4F-x system are further enhanced by their compatibility with Meridian's PC based SpectraSmart, Network Management and Remote Diagnostic Software System. SpectraSmart supervises the operating parameters of the transmission system such as status on video levels, sync, carrier detect, voltage, temperature, optical levels, data activity etc.. See the SpectraSmart brochure for more details.

CONFIGURATIONS

The DT/DR-4V/4F-x systems are available as rack mount cards and modules that can be installed in all of Meridian's card chassis, desk chassis and 19" racking frames. These systems can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be made a standalone system by using the SR-1002, 2 slot desk / wall mount chassis (87VAC-264VAC)

MARKETS

- ✓ Security and Surveillance
- ✓ Intelligent Transportation System (ITS)
- ✓ Access Control Systems
- ✓ Campus Lecture Networks
- ✓ Pro. Video / Audio

SPECIFICATIONS

Video

Format	NTSC, PAL, SECAM
Voltage/Impedance	1 Vp-p, 75 Ohm, 1.5 Vp-p max.
Bandwidth	5 Hz to 6.8 MHz @ -3 dB
Differential Gain	<0.6%
Differential Phase	<0.3°
SNR for 8-Bit Video	>60 dB (weighted)*
SNR for 10-Bit Video	>67 dB (weighted)*
Return Loss	>30 dB
Field Tilt	< 0.5%

Data

Formats	RS-422, Manchester, Bi-Phase
Rate	DC to 1 Mb/s
Bit Error Rate	10 ⁻⁹ *

Optical

Fiber Data Rate	500 Mb/s
-----------------	----------

Connectors

Video	75 Ohm BNC (Gold Center Pin)
Optical	ST, FC
Power	See SR-1000 Brochure for details
Data	DB9 Female

Power **

Card	9 Watts
------	---------

Indicators (LEDs)

1 - Green	Power On
1 - Bi-color	TX Carrier/ Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
1 - Bi-color	RX optical signal - Present / Absent
4 - Bi-color	Video Present / Overload
4 - Green	Sync. Present
4 - Green	Data Present

Physical

Dimensions:	
Card	44 (W) x 127(D) x 160 (H) mm (1.7 x 5.0 x 6.3 inch)
Weight:	
Card	540 gms (1.2 lb.)
No. of Slots	2

Environmental

Operating Temperature	-34°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing



Quality

MTBF	>240,000 hours @ Ground Fix 35°C per MIL217F
------	---

* measured @ max. optical budget

** Due to variations of drivers and diagnostic options,
power shown @ max value

Part Numbers:



OPTICAL

Meridian Optical Code	Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)	Max Distance (Km)
2	Multimode (FP Laser) 62.5 / 125	-3	-24	21	1300 / 850	ST	23	1
5	Single-mode (FP Laser) 9 / 125	-3	-24	21	1310 / 1550	ST, FC	23	60

Meridian Technologies Inc.

700 Elmont Road. • Elmont, NY 11003 • 516. 285. 1000 • FAX 516. 285. 6300 • E-mail sales@meridian-tech.com
Visit our web side: www.meridian-tech.com

ver. 10/2017 B