

**Aiphone IS Hardware-Compatible Fiber Optic
Connectivity between Aiphone IS
Door Stations and IS-CCU**

**FEATURES:**

- Compatible with Aiphone IS series exchange-based installations (IS-CCU)
- Single RJ-45 connector interface
- Real Time Video, Audio and Control Function Transmission
- One-way Video channel
- Bi-directional Audio
- Embedded Data channel for signal flow control
- Wide operating temperature range ideal for outdoor installations
- Wide Optical Dynamic Range: Eliminates need for optical attenuators
- Controlled laser output for stable operation
- Local LED Status Indicators to monitor critical diagnostic & performance parameters
- ST, FC Optical Connector
- Hot Swappable Cards

DESCRIPTION:

The Meridian FT/FR-IS-DV-x product provides a simple, compact fiber optic transport system which seamlessly interfaces the Aiphone IS door stations with the IS-CCU or other exchange units hardware interconnect applications.

The high-quality, cost-effective transport system provides a long distance solution for campuses, parking lots, stairwells, and other remote locations.

This product series ensures an easy, user-friendly interface between the Aiphone IS Series equipment and the fiber optic infrastructure for hardware Aiphone IS applications.

A single RJ-45 connection is used to interface this Meridian unit with the corresponding Aiphone equipment. These products are available for operation over one multimode or singlemode fiber.

CONFIGURATIONS:

This product series is available as rack mount cards that can be installed in any of Meridian's desk chassis or in 19" racking frames. This system can be transformed in to a standalone module by utilizing Meridian's SR-500 chassis frame.

MARKETS:

- Security and surveillance
- Access Control

