


**HARDENED 10-PORT MANAGED LAYER 2 GIGABIT ETHERNET SWITCH WITH 8x10/100BASE-T(X) RJ45 PORTS + 2x1000BASE-X SFP PORTS**

**MANAGED ETHERNET SWITCH**

## FEATURES

- 8x10/100Base-T(X), IEEE 802.3af/at PoE compliant ports and 2x100/1000Base-X SFP ports
- M-Ring (recovery time≤15ms), RSTP/STP and MSTP for network redundancy
- Supports IPv4/IPv6
- Supports web interface management, CLI-Console/Telnet,SNMPv1/v2/v3, RMON/System syslog
- Supports IEEE802.1Q VLAN/MAC based VLAN/Protocol based VLAN/ IP subnet based VLAN/QinQ/GVRP/MVR
- Supports Port-based IEEE802.1X/Single and multiple IEEE802.1X/ MAC-based authentication/VLAN Assignment/ IP source guard/RADIUS/TACACS+/ACL/SSHv2/HTTPS
- Supports ITU-T G.8032 Ethernet Ring Protection
- Supports IGMP v1/v2/v3 Snooping, MLD v1/v2 Snooping
- Supports DHCP Server/Client/Relay/snooping
- Supports DNS client/proxy
- Supports LACP/Link Aggregation Static
- Supports port mirroring, port speed limit, broadcast storm control
- Supports two 2.5G fiber ports (optional 1G)
- EMC industrial level 4
- IP40 protection, metal housing

## DESCRIPTION

The Meridian MS10FT8GX2 is a managed redundant ring PoE Ethernet switch with 8x10/100Base-T(X) ports with PoE+ function and 2x100/1000Base-X SFP ports with complete support of Ethernet redundancy protocol. M-Ring (recovery time≤15ms). The MS10FT8GX2POEH is the P.S.E. version of the switch and supports Power over Ethernet, ability to transmit electrical power with data to remote devices over standard twisted-pair cable. This switch has eight 100Base-T(X) 30Watts P.S.E. (Power Sourcing Equipment) ports and two 1000Base-X ports, which are fully compliant with IEEE 802.3at, IEEE802.3 af standard. This switch can be managed using web browser interface or optional windows utility - SpectraVISION. The switch is designed to work in wide operating temperature from -40 °C to 75 °C, to make it completely suitable for harsh environments.

## MARKETS

- \* Highway monitoring/communication systems
- \* City intelligent transportation systems
- \* Rail transportation monitoring/communication systems
- \* Large-scale industrial communication systems
- \* Railway electric industry control systems
- \* Thermal power industrial control systems
- \* State grid industrial communication systems

## SPECIFICATIONS

Physical Ports		LED indicators	
10/100Base-T(X) Ports in RJ45 Auto MDI/MDIX	8	Power	Green LED: On - Power is On, Off - Power is Off.
100/1000Base-X SFP port	2	System Indicator	Green LED: On - The system is On, Off - The system is Off.
Technology		POE Indicator	Green LED: On - POE is active, Off - POE is not active.
Ethernet Standards	IEEE802.3i/802.3u/802.3ab/802.3z/802.3x/802.3ad/802.1p/802.1q/802.1d/802.1w/802.1s/802.1ad/802.3az/802.1x/802.1ab, IEEE802.3af-2003, IEEE802.3at-2009	10/100Base-T(X) RJ45 Port Indicator	Yellow LED: On - The port speed is 100Mbps. Off - The port speed is 10Mbps. Green LED: On and Blinking - Port LINK UP, data is transmitted. On - No Blinking - Port LINK UP Off - Port LINK DOWN
Protocol	M-Ring, IGMP v1/v2/v3 Snooping, GVRP, SNMPv1/2/3, MLD v1/v2 Snooping, DHCP Server/Client/Relay/snooping, RMON, HTTPS, Telnet, System syslog, SSHv2, DNS client/proxy, CLI-Console, Q-in-Q, RADIUS, TACACS+, ACL	1000Base-X SFP Port	Green LED: On - Link/Act is active: On and Blinking-Port LINK UP, data is transmitted. On-Port LINK UP Off-Port LINK DOWN
MIB	MIB-II, Ethernet-Like MIB, Q-BRIDGE MIB, Bridge MIB, RSTP MIB, RMON MIB Group 1, 2, 3, 9	Power	
DDM Function	Tx/Rx Optical Power and Temperature control	Power redundancy	Optional redundant dual inputs
Flow Control	IEEE802.3x flow control, back pressure flow control	Input Voltage	48VDC
Switch Properties		Full Load	10W
Priority Queues	8	Overload Current Protection	Yes
Maximum No. of Available VLANs	4094	Reverse Polarity Protection	Yes
VLAN ID Range	1-4094	Connection	7-Pin terminal block
MAC Table Size	8K	Physical Characteristic	
Packet Buffer Size	4Mbit	Enclosure	IP40 rated metal enclosure, fanless
Packet Forwarding Rate	4.16Mpps	Dimension (W x D x H)	85(W)x105(D)x155(H) mm (3.35 x 4.13 x 6.10 inch)
Switching delay	<5µS	Weight (g)	1000 g ( 2.2 lb)
Interfaces		Mounting	DIN-Rail / Panel
SFP Port	100/1000Base-X, SFP interface	Environmental	
RJ45 Port	10/100Base-T(X) auto negotiation	Storage Temperature	-40 to 85°C (-40 to 185°F)
802.3af/at PoE Port	Up to 30W on each PoE port, 720mA	Operating Temperature	-40 to 75°C (-40 to 167°F)
Console Port	Micro USB connector, RS232 TX/RX	Operating Humidity	5% to 95% Non-condensing
Alarm Contact	2-pin relay output with current carrying capacity of 0.5A@60V	Regulatory approvals	
Transmission Distance		EMI	FCC Part15 Subpart B Class A/EN55022 Class A
Twisted pair	100m(Adopt standard CAT5, CAT5e)	EMS	EMS: EN61000-4-2 (ESD) Level 3, EN61000-4-3 (RS) exceeds Level 3, EN61000-4-4 (EFT) Level 3, IEC 61000-4-5 (Surge) Level 3, IEC 61000-4-6 (CS) Level 2, IEC 61000-4-8 IEC 61000-4-11, IEC 61000-4-16
Multi-mode	1310nm 5KM(100M)	Shock	IEC60068-2-27
Single mode	1310nm 40KM/60KM(100M) 1550nm 60KM/80KM(100M)	Free Fall	IEC60068-2-32
		Vibration	IEC60068-2-6
		Safety	EN60950-1

Ordering Information		Packing List	
Description	<b>MS10FT8GX2 - Hardened 10-port managed Layer 2 Gigabit Ethernet switch with 8x10/100Base-T(X) RJ45 ports + 2x1000Base-X SFP ports</b>	MS10FT8GX2	1
SFP Options	<b>Refer to Optical SFP Data Sheet for part numbers and ordering information</b>	Wall-Mount Kit	1
SpectraVISION Software	<b>Consult factory for pricing and availability</b>	Manual CD	1
		Din-Rail Kit (attached)	1