


**Digitally Encoded One 10-Bit 10 MHz Video
with Full Duplex Multi-Protocol Data**



FEATURES:

- 10 Bit 10MHz Video Digital Encoding
- Real Time Video and Data Transmission
- Low Power Consumption
- High Efficiency, Isolated Power Supply
- Meets RS-250C Short Haul Transmission Specifications
- NTSC, PAL, SECAM Compatible
- Full Duplex Multiprotocol Data Channel Supports RS-232, RS-422 & RS-485 (2 & 4-wire)
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for both Multimode and Singlemode modules
- Surface Mount Technology (SMT) for High
- Reliability and Repeatability
- Local LED Status Indicators to Monitor Critical
- System Parameters
- ST, FC Optical Connector
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range
- Meets NEMA TS1 / TS2-2003 & CALTRANS Specifications
- 75 Ohm BNC Video Connector (Gold Center Pin)
- Meets EIA RS-170, RS-343A Formats
- Screw Terminal Connector for Data

DESCRIPTION:

This NTNR-1U1G/1G-x module incorporates an all-digital encoding technology and transmits following signals:

1. One real-time, high quality, 10-bit 10 MHz video
2. One channel of user selectable, full duplex RS-232, RS-485 (2 or 4 wire), RS-422, Manchester, Bi-Phase or in combination

Module belongs to new **DigiCool™** series which features very Low Power Consumption and Isolated High Efficiency Power Supply. NTSC, PAL and SECAM video formats are all seamlessly supported. Standard 5-pin terminal blocks are used for easy connection of the data channel interface. These single fiber, laser based systems are available in both, Multimode and Singlemode modules.

Note: See the FT/FR-1U1G/1G-x data sheet for the complementary rack mount card version of this module.

CONFIGURATIONS:

The NTNR-1U1G/1G-x products are available in small stand-alone modules for easy mounting on walls, shelves and other convenient flat surfaces.

MARKETS:

- ✓ Intelligent transportation systems (ITS)
- ✓ Security and surveillance
- ✓ Access Control

SPECIFICATIONS:

Video

Format	NTSC, PAL, SECAM
Voltage/Impedance	1 Vp-p, 75 Ohm, 1.5 Vp-p max.
Bandwidth	5 Hz to 10 MHz @ -3 dB
Linearity	<1%
Differential Gain	<0.6%
Differential Phase	<0.3°
SNR	>67 dB (weighted)*
Return Loss	>30 dB
Field Tilt	< 0.5%

Data

Formats	RS-232 w/ full speed handshake, RS-485, RS-422, Manchester or Bi-Phase
Data Rate (RS-232).....	DC to 125 Kb/s
Data Rate (RS-422, RS-485)..	DC to 250 Kb/s
Bit Error Rate	10 ⁻⁹ *

Optical

Fiber Data Rate	270 Mb/s
-----------------------	----------

Connectors

Video	75 Ohm BNC (Gold Center Pin)
Optical	ST - MM(default), FC - SM(default)
Power (module)	2-pin Screw Terminal
Data	5-pin Screw Terminal

Power **

Input Power (default)	12-24VAC / DC - 2.8 W WP-24 wall adapter (not included)
Input Power (optional)	5VDC - 2.5 W WP-5 wall adapter (not included)

Indicators

1 - Green	Power On
1 - Bi-color	TX Carrier/ Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
1 - Bi-color	Video Present / Overload
1 - Green	Video Sync. Present
1 - Green	Tx Data Present
1 - Green	Rx Data Present

Physical

Dimensions (Module)	117 mm (3.6") L, 60 mm (2.4") W 25 mm (1") D
Weight (Module)	150 gms (0.34 lb)


Enviromental

Operating Temperature ...	-40°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing

Quality

MTBF	>170,000 hours @ Ground Fix 35°C per MIL217F
------------	---

Part Numbers:



* measured @ max. optical budget

** Due to variations of drivers and diagnostic options, power shown @ max value



OPTICAL:

Meridian Optical Code	Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)	Max Distance (Km)
2	Multimode (FP Laser) 62.5 / 125	-5	-28	23	1300 / 850	ST	28	3.5
5	Singlemode (FP Laser) 9 / 125	-5	-28	23	1310 / 1550	ST, FC	28	65

Meridian Technologies Inc.

700 Elmont Road. • Elmont, NY 11003 • 516. 285. 1000 • FAX 516. 285. 6300 • E-mail sales@meridian-tech.com
www.meridian-tech.com

ver 06/2016 F