


**Two Channels of Digitally Encoded
8 or 10 Bit Video****FEATURES:**

- One Slot Digital Module Design
- 8 or 10 Bit Video Digital Encoding
- Real Time Video Transmission
- 7 MHz Video Bandwidth
- Meets RS-250C Short Haul (10 Bit) and Medium Haul (8 Bit) Transmission Spec.
- NTSC, PAL, SECAM Compatible
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for Multimode and Singlemode
- Surface Mount Technology (SMT) for High Reliability and Repeatability
- *SpectraSmart™* Network Management Compatible
- Local LED Status Indicators to Monitor Critical System Diagnostics for Performance Parameters
- ST, FC Optical Connector
- Hot Swappable Cards
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range.
- 75 Ohm BNC Video Connector (Gold Center Pin)
- Meets EIA RS-170, RS-343A Formats

DESCRIPTION:

This module in the **SV** product family incorporates an all-digital encoding technology that transmits two real-time, simplex 8 bit or 10 bit video channels in one direction over one optical fiber. NTSC, PAL and SECAM video formats are all seamlessly supported. These single fiber, laser based systems are available in both, Multimode and Singlemode modules. The **SV** series is also compatible with Meridian's *SpectraSmart* Network management and diagnostic PC based system. See the *SpectraSmart* brochure for additional details

CONFIGURATIONS:

The **SV** product family is available as rack mount cards and modules that can be installed in any of Meridian's desk chassis or in 19" racking frames. This system can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be transformed in to a standalone module by utilizing an SR-500/S (standard configuration) or an SR-1000/S.

MARKETS:

- ✓ Intelligent transportation systems (ITS)
- ✓ Security and surveillance
- ✓ Access Control

SPECIFICATIONS:

Video

Format	NTSC, PAL, SECAM
Voltage/Impedance	1 Vp-p, 75 Ohm, 1.5 Vp-p max.
Bandwidth	5 Hz to 6.8 MHz @ -3 dB
Differential Gain	<0.6%
Differential Phase	<0.3°
SNR (8 Bit)	>60 dB (weighted)*
SNR (10 Bit)	>67 dB (weighted)*
Return Loss	>30 dB
Field Tilt	< 0.5%

Optical

Fiber Data Rate (8 Bit)	250 Mb/s
Fiber Data Rate (10 Bit)	500 Mb/s

Connectors

Video	75 Ohm BNC (Gold Center Pin)
Optical	ST, FC
Power (module)	See SR-500 Brochure for details

Power **

Card	4 Watts
------------	---------

Indicators (LEDs)

1 - Green	Power On
1 - Bi-color	TX Carrier/ Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
2 - Bi-color	Video Present / Overload
2 - Green	Video Sync. Present

Physical

Dimensions (Card)	160 mm (6.3") L, 127 mm (5") W 20mm (0.80") W
Weight (Card)	450 gms (16 Oz)
No. of Slots	1
Module	See SR-500 Brochure


Enviromental

Operating Temperature ...	-34°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing

Quality


MTBF	>200,000 hours @ Ground Fix 35°C per MIL217F
------------	---

Part Numbers:



* measured @ max. optical budget

** Due to variations of drivers and diagnostic options, power shown @ max value



OPTICAL:

Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)
Multimode (FP Laser) 62.5 / 125	-5	-29 (8 Bit) -26 (10 Bit)	24 (8 Bit) 21 (10 Bit)	1300 / 850	ST	24
Singlemode (FP Laser) 9 / 125	-5	-29 (8 Bit) -26 (10 Bit)	24 (8 Bit) 21 (10 Bit)	1310 / 1550	ST, FC	24

Meridian Technologies Inc.

700 Elmont Road. • Elmont, NY 11003 • 516. 285. 1000 • FAX 516. 285. 6300 • E-mail sales@meridian-tech.com
www.meridian-tech.com

ver 04/05 B