

**Digitally Encoded Full Duplex
Multi-Protocol Data Channel**

Full Duplex or
Combination of:
RS 232
RS 422
BI-PHASE
MANCHESTER

FEATURES:

- One slot digital module design
- Real Time Data Transmission
- Full Duplex Multiprotocol Data Channel
- Wide Optical Dynamic Range: Eliminates Need For Optical Attenuators
- Laser Based Systems for Multimode and Singlemode
- Surface Mount Technology (SMT) for High Reliability and Repeatability
- *SpectraSmart™* Network Management Compatible
- Local LED Status Indicators to Monitor Critical System Diagnostics for Performance Parameters
- ST, FC Optical Connector
- Hot Swappable Cards
- Laser Back - Biased Photo Detector Circuitry for Stable Optical Output Over Full Temperature Range.
- Meets EIA RS-170, RS-343A Formats
- 3-pin Screw Terminal Connectors for Data

DESCRIPTION:

The **SXA/SXB-1G** product incorporates an all-digital encoding technology that transmits one user selectable, full duplex, RS-232, RS-422, Manchester, Bi-Phase data channel. Standard 3-pin terminal blocks are used for easy connection of the data channel interface. These single fiber, laser based systems are available in both, Multimode and Singlemode modules. The **SXA/SXB-1G** product is also compatible with Meridian's *SpectraSmart* Network management and diagnostic PC based system. See the *SpectraSmart* brochure for additional details.

CONFIGURATIONS:

The **SXA/SXB-1G** product is available as rack mount cards and modules that can be installed in either Meridian's desk chassis or in 19" racking frames. This system can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be made a standalone system by using the SR-500/S, SR-1000/s, 1 or 2 slot desk / wall mount chassis (87 VAC- 264VAC)

MARKETS:

- ✓ Intelligent transportation systems (ITS)
- ✓ Security and surveillance
- ✓ Access Control

SPECIFICATIONS:

Data

Formats	RS-232, RS-422, Manchester or Bi-Phase
Data Rate	DC to 125 Kb/s
Bit Error Rate	10 ⁻⁹ *

Optical

Fiber Data Rate	50 Mb/s
-----------------------	---------

Connectors

Optical	ST, FC
Power (module)	See SR-500 Brochure for details
Data	3-pin Screw Terminal

Power **

Card	4 Watts
------------	---------

Indicators (LEDs)

1 - Green	Power On
1 - Bi-color	TX Carrier / Laser Over Current
1 - Bi-color	RX Carrier - Present / Error
1 - Green	Tx Data Present
1 - Green	Rx Data Present

Physical

Dimensions (Card)	160 mm (6.3") L, 127 mm (5") W 20mm (0.80") W
Weight (Card)	450 gms (16 Oz)
No. of Slots	1
Module	See SR-500 Brochure


Enviromental

Operating Temperature ...	-34°C to +74°C
Storage Temperature	-55°C to +85°C
Relative Humidity	0 to 95% Non-condensing


Quality

MTBF	>170,000 hours @ Ground Fix 35°C per MIL217F
------------	---

Part Numbers:



* measured @ max. optical budget
** Due to variations of drivers and diagnostic options, power shown @ max value



FULL DUPLEX OR
COMBINATION OF RS 232,
BI-PHASE, RS 422
OR MANCHESTER
IN/OUT

FULL DUPLEX OR
COMBINATION OF RS 232,
BI-PHASE, RS 422
OR MANCHESTER
IN/OUT

OPTICAL:

Fiber Type/Size (um)	Optical Output (dBm)	Receiver Sensitivity (dBm)	Optical Budget (dB)	Wavelength (nm)	Optical Connector	Optical Dynamic Range (dB)
Multimode (FP Laser) 62.5 / 125	-5	-26	21	1300 / 850	ST	24
Singlemode (FP Laser) 9 / 125	-5	-26	21	1310 / 1550	ST, FC	24