



HARDENED 2 PORT MEDIA CONVERTER**1 PORT 10/100/1000TX (RJ45) + 1 PORT 1000 SFP****MEDIA CONVERTER****FEATURES**

- 10/100/1000 Base-T Ethernet Auto-negotiation
- Full Duplex or Half-duplex Supported
- IEEE 802.3 Compliant
- NTCIP Compatible
- Far End Fault Function
- Link Fault Pass-through Function
- LC Optical Connectors Standard, SC Optional
- Hot Swappable Rack Cards
- SFP Speed Detect
- Auto MDI/MDIX
- Jumbo Frames Support

DESCRIPTION

The SX-1RE-SFP (single-slot rack cards) are Ethernet transceivers designed for bi-directional transmission of 10Base-T Ethernet / 100Base-T Fast Ethernet /1000Base-T GigE Ethernet data over one multimode or singlemode fiber. Since the data rate is auto-negotiated, no internal adjustments or setting are necessary. Distances of 50km can be obtained using singlemode fiber. The SX-1RE-SFP are environmentally hardened and will operate over the standard NEMA TS-2 temperature range - suitable for outdoor installations. LEDs on both the module and rack card indicate power, link speed, activity, laser current and optical signal. Standard shielded RJ-45 connectors are provided for CAT 5 compliance.

The SX-1RE-SFP incorporating industry standard Small Form Pluggable (SFP) optical modules for exceptional product versatility and performance.

The SX-1RE-SFP products are available as rack mount cards and modules that can be installed in either Meridian's desk chassis or in 19" racking frames. This system can be configured in either star (module to rack) or trunking (rack to rack) configurations. These systems can be made a standalone system by using the SR-500, SR-1000, 1 or 2 slot desk/wall mount chassis (87 VAC- 264VAC).

SPECIFICATIONS

Physical Ports		Dimension (W x D x H)	20 (W) x 127 (D) x 160 (H) mm (0.8 x 5.0 x 6.3 inch)
10/100/1000 Base-T(X) Port in RJ45 Auto MDI/MDIX	1	Weight (g)	450 g
1000Base-FX SFP port	1	Environmental	
Technology		Storage Temperature	-40 to 85°C (-40 to 185°F)
Ethernet Standards	IEEE 802.3 CSMA/CD IEEE 802.3i 10Base-T IEEE 802.3u 100Base-T IEEE 802.3ab 1000Base-T	Operating Temperature	-40 to 75°C (-40 to 167°F)
Data Rate	10/100/1000 Mb/s	Operating Humidity	5% to 95% Non-condensing
Bit Error Rate	Better than 10 ⁻⁹	Regulatory approvals	
Fiber Data Rate	1250 Mb/s	EMI	FCC Part 15, CISPR (EN55022) class A
LED indicators		EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
Power On	1 - Green (normal) - when power is applied to the module	Shock	IEC60068-2-27
RX Link/ACT	Study Green - link established on the fiber port Blinks Green - activity is detected on the fiber port OFF - fault is detected	Free Fall	IEC60068-2-32
TX Link/ACT	Study Green - link established on the cooper port Blinks Green - activity is detected on the cooper port OFF - fault is detected	Vibration	IEC60068-2-6
Power		Safety	EN60950-1
Power Consumption (Typ.)	4 Watts	Warranty	
Overload Current Protection	Present	5 Years	
Physical Characteristic			
Enclosure	Rack Card		

Ordering Information	
Description	SX-1RE-SFP - 10/100/1000 Media converter, 1 Port 10/100/1000TX (RJ45) + 1 Port 1000 SFP
SFP Options	<p>Refer to Optical SFP Data Sheet for complete part numbers and ordering information or</p> <p>go to: WWW.MERIDIAN-TECH.COM -> PRODUCTS -> ACCESSORIES -> SFP OPTICAL DEVICES</p> <p>Recommended optical speed for this product is 1.25 Gb/s.</p>

Packing List	
SX-1RE-SFP	1
Quick Installation Guide	1