

**HARDENED 10-PORT LAYER 2 UNMANAGED GIGABIT ETHERNET SWITCH WITH
 8x10/100/1000BASE-T(X) RJ45 PORTS + 2x1000BASE-X SFP PORTS**

UNMANAGED ETHERNET SWITCH

FEATURES

- IEEE 802.3af/at PoE compliant 8x10/100/1000Base-T(X) and 2x100/1000Base-X SFP ports
- Support for IPv4 and IPv6
- Supports 1588 ptpv2, Sync-E
- Ethernet Ring Protection with STP/RSTP/MSTP/ITU-TG.8032
- IGMP v1/v2/v3 and MLD v1/v2 Snooping for filtering multicast traffic
- IEEE802.1Q VLAN/MAC based VLAN/Protocol based VLAN/ IP subnet based VLAN/QinQ/GVRP/MVR is supported
- DHCP Server/Client/Relay/Snooping for IP security management
- Port-based IEEE802.1X/Single and multiple IEEE802.1X/MAC-based authentication/VLAN Assignment/ IP source guard/RADIUS/TACACS+/ACL/SSHv2/HTTPS
- DNS client/proxy is supported
- LACP/Link Aggregation Static for increases throughput
- Supports Port mirroring, port speed limits, broadcast, Storm control
- Two 2.5G fiber ports with backward 1G compatibility
- EMC industrial level 4
- IP40 protection, metal housing

DESCRIPTION

The Meridian US10GT8GX2 is unmanaged Gigabit Ethernet switch with 8x10/100/1000Base-TX and 2x1000Base-X Ports.

The US10GT8GX2POEH is the P.S.E. version of the switch and supports Power over Ethernet, ability to transmit electrical power with data to remote devices over standard twisted-pair cable. The US10GT8GX2POEH has eight 1000Base-T(X) 30Watts P.S.E. (Power Sourcing Equipment) ports and two 1000Base-X ports, which are fully compliant with IEEE 802.3at, IEEE802.3 af standard.

The switch is designed to work in wide temperature range from -40°C to 75°C, to make it completely suitable for harsh environments.

MARKETS

- * Highway monitoring/communication systems
- * City intelligent transportation systems
- * Rail transportation monitoring/communication systems
- * Large-scale industrial communication systems
- * Railway electric industry control systems
- * Thermal power industrial control systems
- * State grid industrial communication systems

SPECIFICATIONS

Physical Ports		Transmission Distance	
10/100/1000Base-T(X) Ports in RJ45 Auto MDI/MDIX	8	Twisted pair	100m(Adopt standard CAT5, CAT5e)
100/1000Base-X SFP port	2	Multi-mode	1310nm 5KM(100M), 850nm 550M(1000M)
Technology		Single mode	1310nm 40KM/60KM(100M) 1550nm 60KM/80KM(100M) 1310nm 10KM/40KM(1000M) 1550nm 60KM/80KM(1000M)
Ethernet Standards	IEEE802.3i/802.3u/802.3ab/802.3z/802.3x/802.3ad/802.1p/802.1q/802.1d/802.1w/802.1s/802.1ad/802.3az/802.1x/802.1ab, IEEE802.3af-2003, IEEE802.3at-2009		
Protocol	IGMP v1/v2/v3 Snooping, GVRP, SNMPv1/2/3, MLD v1/v2 Snooping, DHCP Server/Client/Relay/snooping, RMON, HTTPS, System syslog, SSHv2, DNS client/proxy, CLI-Console, Q-in-Q, RADIUS, TACACS+, ACL		
DDM Function	Tx/Rx Optical Power and Temperature control		
Flow Control	IEEE802.3x flow control, back pressure flow control		
Switch Properties		LED indicators	
Priority Queues	8	Power	Green LED: On - Power is On, Off - Power is Off.
Maximum No. of Available VLANs	4094	System Indicator	Green LED: On - The system is On, Off - The system is Off.
VLAN ID Range	1-4094	POE Indicator	Green LED: On - POE is active, Off - POE is not active.
MAC Table Size	8K	10/100/1000Base-T(X) RJ45 Port Indicator	Yellow LED: On - The port speed is 1000Mbps. Off - The port speed is 10Mbps or 100Mbps. Green LED: On and Blinking - Port LINK UP, data is transmitted. On - No Blinking - Port LINK UP Off - Port LINK DOWN
Packet Buffer Size	4Mbit	1000Base-X SFP Port	Green LED: On-Port LINK UP On and Blinking-Data is transmitted. Off-Port LINK DOWN
Packet Forwarding Rate	14.88Mpps	Power	
Switching delay	<5μs	Input Voltage	48VDC redundant inputs
Interfaces		Full Load	15W max
SFP Port	100/1000Base-X, SFP interface	Overload Current Protection	Yes
RJ45 Port	10/100/1000Base-T(X) auto negotiation	Reverse Polarity Protection	Yes
802.3af/at PoE Port	Up to 30W on each PoE port, 720mA	Connection	7-Pin terminal block
Console Port	Micro USB connector, RS232 TX/RX	Physical Characteristic	
Alarm Contact	2-pin relay output with current carrying capacity of 0.5A@60V	Enclosure	IP40 rated metal enclosure, fanless
		Dimension (W x D x H)	55(W)x128(D)x155(H) mm (2.16 x 5.03 x 6.10 inch)
		Weight (g)	1500 g (3.3 lb)
		Mounting	DIN-Rail / Panel
		Environmental	
		Storage Temperature	-40 to 85°C (-40 to 185°F)
		Operating Temperature	-40 to 75°C (-40 to 167°F)
		Operating Humidity	5% to 95% Non-condensing

Ordering Information		Packing List	
Description	US10GT8GX2 - Hardened 10-port unmanaged Gigabit Ethernet switch with 8x10/100/1000Base-T(X) RJ45 ports + 2x1000Base-X SFP ports US10GT8GX2POEH - Hardened 10-port unmanaged P.S.E. Gigabit Ethernet switch with 8x10/100/1000Base-T(X) PoE+ ports + 2x1000Base-X SFP ports	US10GT8GX2 or US10GT8GX2POEH	1
SFP Options	refer to Optical SFP Data Sheet for complete part numbers and ordering information	Wall-Mount Kit	1
		Manual CD	1
		Din-Rail Kit (attached)	1